



**CAPSTONE
MINING CORP.**

SURFACE DRILL HOLE INTERCEPTS

Hole #	From (m)	To (m)	Length (m)	True Width (m)	Au (g/t)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)
CG-04-01	287.50	296.00	8.50	3.20	0.03	126.6	1.93	1.06	2.85
CG-04-02	306.80	311.95	5.15	4.20	0.22	129.1	2.89	0.12	0.73
CG-04-03	326.20	341.40	15.20	14.90	0.08	99.6	4.35	0.01	0.27
CG-04-04 including	340.00 346.75	349.75 349.00	9.75 2.25	7.24 2.10		40.9 67.3	2.12 3.42		2.60 4.13
CG-04-05 including	351.00 353.87	356.75 356.25	5.75 2.38	5.47 2.38		62.9 135.3	1.06 2.46		0.85 1.61
CG-04-06 including	417.40 417.40	426.30 419.30	8.90 1.90	6.85 1.77		62.2 185.4	1.49 2.91		0.23 1.17
CG-04-07 including	377.00 377.00	380.00 379.00	3.00 2.00	2.65 1.76		82.1 119.1	0.85 1.19		13.93 10.45
CG-04-08	336.80	340.00	3.20	2.80		97.8	1.60		1.60
CG-04-10 including	483.30 488.10	496.20 495.30	12.90 7.20	9.00 5.00		107.6 148.1	2.50 3.40		1.90 2.10
CG-04-11 including	367.60 369.70	373.90 372.00	6.30 2.30	5.60 2.00		126.1 258.8	2.50 4.30		2.60 2.40
CG-04-12 including	291.50 291.50	296.80 295.00	5.30 3.50	4.00 2.70		115.9 153.6	2.90 3.70		0.90 1.20
CG-04-13 including	321.80 330.40	333.50 333.50	11.70 3.10	8.90 2.40		134.0 279.1	1.40 1.80		1.60 1.40
CG-04-15 including	294.90 296.60	302.80 299.10	7.90 2.50	6.00 1.90		75.5 133.6	4.90 8.70		0.20 0.80
CG-04-16	317.40	321.90	4.50	3.90		62.2	1.50		0.50
CG-04-18 including	344.40 347.20	361.40 354.90	17.00 7.70	14.10 6.40		82.2 145.6	3.90 7.00		0.40 0.40
CG-04-19 including	190.40 191.80	198.30 194.10	7.90 2.30	6.00 1.70		58.2 106.0	1.60 4.40		0.40 0.50
CG-04-20 including	312.70 317.60	321.00 320.70	8.30 3.10	6.80 2.60		100.3 138.7	1.40 1.90		4.80 2.70
CG-04-21	464.60	476.80	12.20	8.50		11.1	0.20		5.90
CG-04-22	450.70	452.30	1.60	1.40		30.2	1.70		0.10
CG-04-23	135.00	135.70	0.70	0.60		30.5	0.00		3.80
CG-04-24	417.00	417.90	0.90	0.80		18.2	0.10		9.40
CG-04-25	267.80	269.40	1.60	1.40		0.2	0.20		4.50
CG-04-26 including	647.00 647.00	653.20 649.60	6.20 2.60	4.60 1.90		32.0 41.4	2.00 2.80		0.10 0.10
CG-04-27 including	589.80 585.80	593.70 593.70	3.90 7.90	5.90 2.90		62.1 91.6	1.80 2.50		0.80 1.40
CG-04-28 including	639.30 642.00	644.40 644.40	5.10 2.40	3.80 1.80		40.8 62.3	2.00 3.00		0.10 0.20
CG-04-29 including	510.20 510.50	512.90 513.90	2.70 3.40	3.20 2.10		158.9 219.5	5.50 7.60		1.10 0.90
CG-05-33	666.20	668.20	2.00	1.70		14.0	0.20	0.00	8.00
CG-05-34 and	104.10 565.90	111.00 572.50	6.90 6.60	6.10 6.00		37.0 40.0	0.00 1.70	3.00 0.00	6.90 0.10
CG-05-35	252.60	254.30	1.70	1.50		79.8	0.90	0.00	3.70
CG-06-38	768.75	773.50	4.75	3.88	0.07	53.5	1.36	0.03	0.06
CG-07-41	793.00	799.50	6.50	2.89	0.00	49.5	0.13	0.04	0.04

True widths are estimated by correcting for strike and dip of the vein with regard to the bearing and inclination of the drill hole.

Drill holes CG-04-09, CG-04-14, CG-04-17, CG-05-30, CG-05-31, CG-05-32, CG-06-39, CG-07-40 and CG-07-42 were anomalous but did not intersect any significant mineralization.

Where no assay is recorded an intercept was not calculated.